

Respiratory protection

September 10, 2010 PGM-Head

Product data sheet cup shape mask FFP3 - uvex silv-Air 2310



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, 90766 Fürth, Germany

Product features	 Optimised shape Soft material edges for more high wearing comfort 4-point headband for a comfortable, secure fit Exhalation valve for reduced build-up of heat and moisture inside the mask Flexible and adjustable nose piece Mask fulfils the requirements of the dolomite dust test (D) Compatible with uvex safety eyewear The half sealing lip provides good fitting combined with high wearing comfort 	
Materials	Head band: elastic textile Nose piece: aluminum Headband clips: PP Filter / mask: Melt Blown PP, Polyester Sealing lip: PVC foam Valve: ABS	

Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values.	Welding, soldering, high concentrations of very hazardous and microscopic respirable dust and with chemical compounds that contain beryllium, stibium, arsenic, cadmium, cobalt, nickel, platinum, radium or strychnine.
Weight	24 g
Standard	EN 149:2001 + A1:2009

Versions/Colour:

Artkle-No.	Colour/Version	Retail unit
8732.310	cup shape mask FFP3, white with valve	15 pieces per box