

**Product Datasheet model i-vo 9160 043****UVEX ARBEITSSCHUTZ GMBH,  
Würzburger Str. 181-189, D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* Duo-spherical lens</li><li>* Duo component technology</li><li>* Extremely comfortable for all-day wear</li><li>* Shock absorbing brow guard</li><li>* Indirect ventilation</li><li>* Quattroflex patented temple</li><li>* Adjustable temple length and lens inclination</li><li>* Grey lens tint ensures perfect colour recognition</li></ul>
<b>Technical details</b>	
<b>Frame</b>	
Material	<b>Front piece</b> TPU/TPE
Colour	black/green
Material	<b>Side piece</b> PC
Features	length adjustability
Colour	black

Material	<b>Temple</b>
Features	TPU/TPE
Colour	quattroflex temple black/green
Manufacturer's ID code	<b>Marking</b>
Applicable EN norm	W
Low-energy impact	166
Resistance to high speed particles at extremes of temperat.	F (45 m/s)
Conformity symbol	T
No. of certificat. Body	CE 0196
<b>Lens</b>	
Material	PC
Thickness	3 mm
Coating	infradur AF
Colour	grey
Filter	<b>Marking</b>
Manufacturer's ID code	3 (DIN EN 169)
Optical class	W
Low-energy impact	1
Resistance to high speed particles at extremes of temperat.	F (45 m/s)
Surface resistance to fine particles	T
Antifog	K
Conformity symbol	N CE

**Miscellaneous**

Weight

33 g

Packing

5 spectacles per box

200 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 169