

**Product Datasheet model i-3 9190 275****UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

|   |  |
|---|--|
| <b>Product characteristics</b>  | <ul style="list-style-type: none"><li>* Innovative protective spectacle, perfectly fit the face</li><li>* Individually adjustable side arms with variable inclination</li><li>* Integrated Softflex zone ensures outstanding wearer comfort for all head sizes</li><li>* Softflex nose piece with flexible adjustment ensures comfortable, pressure-free fit and remain firmly in place</li><li>* Soft ear and Softflex bridge pieces ensure a secure fit in any situation</li></ul> |
| <b>Technical details</b><br><br>Frame<br><br>Material<br>Features<br>Colour | <br><br>Front piece/Temple<br>TPU/TPE<br>variable inclination, individually adjustable<br>anthracite-blue  |

|   |                      |
|---|----------------------|
| Manufacturer's ID code  | <b>Marking</b><br>W  |
| Applicable EN norm  | 166                  |
| Low-energy impact Resistance to high speed particles at extremes of temperat. | F (45 m/s)<br>T      |
| Conformity symbol   | CE                   |
| No. of certificat. body   | 0196                 |
| <b>Lens</b>   |                      |
| Material  | PC                   |
| Thickness   | 2,2 mm               |
| Coating   | supravison HC-AF     |
| Colour  | clear                |
| <b>Marking</b>  |                      |
| Filter  | 2C-1,2 ( DIN EN 170) |
| Manufacturer's ID code  | W                    |
| Optical class   | 1                    |
| Low-energy impact Resistance to high speed particles at extremes of temperat. | F (45 m/s)<br>T      |
| Surface resistance to fine particles  | K                    |
| Antifog   | N                    |
| Conformity symbol   | CE                   |

**Miscellaneous**

Weight

30 g

Packing

5 spectacles per box

160 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 170