

**Product Datasheet model i-3 9190 286****UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

|                                |  |
|--------------------------------|--|
| <b>Product characteristics</b> | <ul style="list-style-type: none"><li>* Innovative protective spectacle, perfectly fit the face</li><li>* Individually adjustable side arms with variable inclination</li><li>* Integrated Softflex zone ensures outstanding wearer comfort for all head sizes</li><li>* Softflex nose piece with flexible adjustment ensures comfortable, pressure-free fit and remain firmly in place</li><li>* Soft ear and Softflex bridge pieces ensure a secure fit in any situation</li></ul> |
| <b>Technical details</b>       |  |
| <b>Frame</b>                   | <b>Front piece/Temple</b>  |
| Material                       | TPU/TPE  |
| Features                       | variable inclination, individually adjustable  |
| Colour                         | anthracite-red   |

|   |                     |
|---|---------------------|
| Manufacturer's ID code                                      | <b>Marking</b><br>W |
| Applicable EN norm  | 166                 |
| Low-energy impact   | F (45 m/s)          |
| Resistance to high speed particles at extremes of temperat. | T                   |
| Conformity symbol   | CE                  |
| No. of certificat. body                                     | 0196                |
| <b>Lens</b>   |                     |
| Material  | PC                  |
| Thickness   | 2,2 mm              |
| Coating   | supravison HC-AF    |
| Colour  | grey                |
| <b>Marking</b>  |                     |
| Filter  | 5-2,5 ( DIN EN 172) |
| Manufacturer's ID code                                      | W                   |
| Optical class   | 1                   |
| Low-energy impact   | F (45 m/s)          |
| Resistance to high speed particles at extremes of temperat. | T                   |
| Surface resistance to fine particles                        | K                   |
| Antifog   | N                   |
| Conformity symbol   | CE                  |

**Miscellaneous**

Weight

30 g

Packing

5 spectacles per box

160 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 172