

Product Datasheet model ultravision 9301 245



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<p>Product characteristics</p>	<ul style="list-style-type: none"> * Anatomical shape and soft material allow close, yet comfortable fit * Fits comfortably over most prescription spectacles * Nose bridge works well with respirators * High-quality, easily adjustable headband * Optically correct lens (EN 166 class 1) does not distort view or cause headaches * Simple lens replacement reduces cost
<p>Technical details</p> <p>Frame</p> <p>Material Features Colour</p> <p>Material Features Colour</p>	<p>Front piece PVC ventilation system black</p> <p>Headband synthetic headband adjustable black/lime</p>

Manufacturer's ID code	Marking W
Applicable EN norm	166
Fiedl of use	3 (drops and splashes of liquid)
Impact resistance	F (45 m/s)
No. of certificat. body	0196
Conformity symbol	CE
Lens	
Material	PC
Thickness	2,1 mm
Coating	infradur PLUS
Colour	green
Filter	Marking 5 (EN 169)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Miscellaneous	
Weight	133 g
Packing	90 pieces in one carton
Standards	DIN EN 166 + DIN EN 169