SAFETY DATA SHEET LYRECO AIR DUSTER 520ML/400MLNET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name LYRECO AIR DUSTER 520ML/400MLNET

Product number 2,974,929,ZP

Internal identification AHFC400LYR_EU; AHFC400LYR_EE; AHFC400LYR_FE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Office Equipment Cleaning Product

this safety data sheet when available

1.3. Details of the supplier of the safety data sheet

Supplier LYRECO

Rue du 19 mars 1962, F-59770

MARLY FRANCE

+33 (0) 3 27 23 64 00

msds@lyreco.com

1.4. Emergency telephone number

Emergency telephone +33 (0) 3 27 23 64 00 This number is serviced during office hours only

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229

Health hazards Not Classified

Environmental hazards Not Classified

Classification (67/548/EEC or F+;R12.

1999/45/EC)

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

LYRECO AIR DUSTER 520ML/400MLNET

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PROPANE 60-100%

CAS number: 74-98-6 EC number: 200-827-9 REACH registration number: 01-

2119486944-21-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+;R12

Press. Gas

BUTANE 10-30%

CAS number: 106-97-8 EC number: 203-448-7 REACH registration number: 01-

2119474691-32-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+;R12

Press. Gas

ISOBUTANE 10-30%

CAS number: 75-28-5 EC number: 200-857-2 REACH registration number: 01-

2119485395-27-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+;R12

Press. Gas

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

levels.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Move affected person to fresh air and keep warm

and at rest in a position comfortable for breathing.

Ingestion Not relevant.

Skin contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

LYRECO AIR DUSTER 520ML/400MLNET

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours in high concentrations are anaesthetic. Symptoms following overexposure may

include the following: Headache. Fatigue. Dizziness. Central nervous system depression.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc.

Unsuitable extinguishing

media

Do not use water, if avoidable.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapours. Containers can burst

violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire

exposed containers cool and disperse vapours.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Do not breathe

vapour.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11

for additional information on health hazards. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See Section 12 for additional information on ecological hazards. Collect

and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

LYRECO AIR DUSTER 520ML/400MLNET

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering

controls

All handling should only take place in well-ventilated areas. Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or

ingredients.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. EN166

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It is recommended that gloves are made of

the following material: Nitrile rubber. Gloves should conform to EN374

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear appropriate clothing to prevent skin contamination.

Hygiene measuresUse engineering controls to reduce air contamination to permissible exposure level. Provide

eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and

before eating, smoking and using the toilet. When using do not eat, drink or smoke.

Respiratory protectionNo specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the

following cartridge: Gas filter, type A2. EN14387

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol. Liquid.

Colourless.

Odour Characteristic.

Flash point -40°C CC (Closed cup).

LYRECO AIR DUSTER 520ML/400MLNET

Upper/lower flammability or

explosive limits

: 1.8

Solubility(ies) Insoluble in water.

Auto-ignition temperature 410/580°C

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not available. Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information No specific health hazards known.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Acute toxicity - fish

No information required.

Acute toxicity - aquatic

No information required.

invertebrates

Acute toxicity - aquatic plants No information required.

Acute toxicity - No information required.

microorganisms

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

LYRECO AIR DUSTER 520ML/400MLNET

12.4. Mobility in soil

Mobility The product contains volatile substances which may spread in the atmosphere.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects The product contains a substance or substances that will contribute to global warming

(greenhouse effect).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion.

Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR

and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons

of less than 30kg gross to be exempt from control providing that they are labelled in

accordance with the requirements of these regulations to show that they are being transported

as Limited Quantities. Aerosols not so packed must show the following

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

AEROSOLS

Proper shipping name

(IMDG)

AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2

ADR/RID subsidiary risk

ADR/RID label 2.1

IMDG class 2.1

IMDG subsidiary risk

ICAO class/division 2.1

ICAO subsidiary risk

LYRECO AIR DUSTER 520ML/400MLNET

Transport labels



14.4. Packing group

ICAO packing group

ADR/RID packing group N/A
IMDG packing group N/A

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

N/A

No.

14.6. Special precautions for user

EmS F-D, S-U

Emergency Action Code

Hazard Identification Number (ADR/RID)

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Control of Substances Hazardous to Health Regulations 2002 (as amended).

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative

occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

work (as amended).

Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and

Directive 91/689/EEC on hazardous waste with amendments.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Guidance

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are known for this product.

LYRECO AIR DUSTER 520ML/400MLNET

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

Issued by David Bray

Revision date 15/05/2015

Revision 2

SDS number 13254

Risk phrases in full R12 Extremely flammable.

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.