

Product Datasheet model pheos 9192 225



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<p>Product characteristics</p>	<ul style="list-style-type: none"> * Modern fashion-look * Duo spherical lens provides excellent all round vision * Eye plus-protection protects the eyebrows through an additional chamfer at the upper range * A slim temple geometry enables a comfortable wearing of earmuffs, helmets and caps * Outstanding ventilation ensures a well eye climate * Temple ends with non-slip components
<p>Technical details</p> <p>Frame</p> <p>Material</p> <p>Features</p> <p>Colour</p>	<p>Front piece/Temple</p> <p>POM/TPE</p> <p>excellent ventilation</p> <p>black-green</p>

Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Conformity symbol	CE
Lens	
Material	PC
Thickness	2,1 mm
Coating	supravison HC-AF
Colour	clear
Filter	Marking 2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Miscellaneous	
Weight	30 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170