

### Product Datasheet model ultrasonic 9302 245



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"> <li>* Panoramic lens shape allows 180° uninterrupted lateral vision</li> <li>* Medium-energy impact 'B' (120 m/s)</li> <li>* Integrated, indirect ventilation allows air movement directly across the lens</li> <li>* Fits comfortably over most prescription spectacles</li> <li>* Simple lens replacement</li> <li>* High-quality, easily adjustable headband</li> </ul>
<b>Technical details</b>  <b>Frame</b>  Material Colour   Material Features Colour	<b>Front piece</b> PP/TPE orange/grey  <b>Headband</b> synthetic headband individually adjustable orange/grey

<b>Manufacturer's ID code</b>	<b>Marking</b> W
<b>Applicable EN norm</b>	166
<b>Field of use</b>	3 (drops and splashes of liquid) 4 (large dust particles) 9 (molten material and hot solids)
<b>Impact resistance</b>	B (120 m/s)
<b>Tested acc. to DIN</b>	DIN
<b>No. of certificat. body</b>	0196
<b>Conformity symbol</b>	CE
<b>Lens</b>	
<b>Material</b>	PC
<b>Thickness</b>	2,2 mm
<b>Coating</b>	supravision HC-AF
<b>Colour</b>	clear
<b>Optical class</b>	1
<b>Filter</b>	<b>Marking</b> 2-1,2 ( DIN EN 170)
<b>Manufacturer's ID code</b>	W
<b>Optical class</b>	1
<b>Impact resistance</b>	B (120 m/s)
<b>Field of use</b>	9 (molten material and hot solids)
<b>Surface resistance to fine particles</b>	K
<b>Antifog</b>	N
<b>Tested acc. to DIN</b>	DIN
<b>Conformity symbol</b>	CE
<b>Miscellaneous</b>	
<b>Weight</b>	80 g
<b>Packing</b>	4 goggles per box 72 pieces in one carton
<b>Standards</b>	DIN EN 166 + DIN EN 170