

## E-A-RSoft™ Yellow Neon™ and Yellow Neon Blasts™ Roll-Down Earplugs



### Product Description

The E-A-RSoft™ Yellow Neon™ and Yellow Neon Blasts™ roll-down earplugs are designed for insertion into the ear canal to help reduce exposure to hazardous levels of noise and loud sound. These products are available in corded and uncorded version.

The Uncorded version is also available in One Touch™ Dispenser format.

### Key Features

- Slow expanding, polyurethane foam
- Extremely soft foam helps provide low pressure inside the ear canal thus increasing comfort and wearability
- Tapered shape conforms quickly to most ear canals- particularly large size
- Excellent sound attenuation characteristics- SNR 36dB
- Particularly suited for low frequency noise
- Vibrant colour- E-A-RSoft Yellow Neon Blasts with flames
- Supplied in re-sealable pillow-pack for ease of use
- Available in both corded and uncorded version

### Applications

The E-A-RSoft™ Yellow Neon™ and Yellow Neon Blasts™ are ideal for high noise exposure levels, and are ideally suited for all frequency noise in a wide range of industrial workplace and leisure environment. Examples of typical applications include:

- Automotive
- Chemical & pharmaceutical manufacture
- Construction
- Heavy engineering
- Metal processing
- Textile manufacture
- Woodworking

### Standard & Approval

The E-A-RSoft™ Yellow Neon™ and Yellow Neon Blasts™ are tested and CE approved against the European Standard EN352-2:1993. These products meet the Basic Safety Requirements as laid out in Annex II of the European Community Directive 89/686/EEC and have been examined at the design stage by INSPEC International Limited, 56 Leslie Hough Way, Salford, Greater Manchester M6 6AJ, UK (Notified Body number 0194).

### Materials

The following materials are used in the manufacture of this product.

Component	Material
Earplugs	Polyurethane Foam
Cord	PVC



### Attenuation values

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mf (dB)	23.7	30.8	36.1	39.2	39.5	35.8	42.1	46.1
sf (dB)	6.7	6.5	6.7	4.7	3.9	4.9	3.1	3.3
APVf (dB)	17.0	24.3	29.4	34.5	35.6	30.9	39.0	42.8

SNR = 36dB      H = 34dB      M = 34dB      L = 31dB

### Key

APVf (dB) = Mf – sf (dB)

Mf = Mean attenuation value

sf = Standard deviation

APVf = Assumed Protection Value

H = High-frequency attenuation value (predicted noise level reduction for noise with L(C) – L(A) = -2dB)

M = Medium-frequency attenuation value (predicted noise level reduction for noise with L(C) – L(A) = +2dB)

L = Low-frequency attenuation value (predicted noise level reduction for noise with L(C) – L(A) = +10dB)

SNR = Single Number Rating (the value that is subtracted from the measured C-weighted sound pressure level, L(C) in order to estimate the effective A-weighted sound pressure level inside the ear).

### Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Occupational Health & Safety  
Products EMEA Division  
3M Svenska AB  
Mammstengsgatan 19  
331 02 Värnamo Sweden  
Visit us: www.3M.eu/OccSafety

Secondary address  
3M Operating Unit  
Address  
City, State, Postal Code  
Country  
Phone  
Fax  
Email  
Website address  
Please recycle.

© 3M 2009. All rights reserved.

Please recycle.  
© 3M 2009. All rights reserved.