Technical data sheet 3476

Specification Swivel chair

| Dimensions in mm | Backrest: | H: | 620 |
|------------------|-----------|-------------|---------|
| | Seat: | H: | 420-550 |
| | | W: | 460 |
| | | D: | 445 |
| | Total: | H: | 1190 |
| | | W (no ArmR) | 460 |
| | | W (ArmR): | 720 |
| | | D: | 680 |
| Packaging data | Weight: | kg | 19,5 |
| | Volume: | m³ | 0,2 |
| | | | |



| Basic equipment | | Benefit |
|-----------------------------|---|---|
| Backrest | Mesh, black with adjustable lumbar support. | The backrest offers an optimum of support because of its 3-dimensional shaped backrest carrier. The backrest doesn't give way, like other standard foam parts. The high density of the foam ensures a long sitting comfort even if you sit more than three hours. The design elements give the chair a very elegant effect. |
| Comfort upholstery | Shaped foam seat hollow and a density of 50 gr/dm³. | Better seating comfort for longer sitting term, as the higher density of the foam avoids to wear out the foam. In addition, it avoids the widening of the veins of the bottom and it encourages the circulation. |
| Column | Gas lift with steel case. | Seat height setting to adapt the seat height to the different body sizes. |
| Mechanic | Synchronous mechanism. The seat and backrest move synchrone to each other, the chair follows the movement of the user in the open state. The movement can be fixed in each desired angle. The counterpressure of the mechanism can be stepless adjusted by a handwheel. | The back has a constant support and the stomach part is relieved. Consequently this avoids to be tensed up and the upright seating position is beeing supported. At the same time a homogene pressure distribution in the vertebra is achieved. By the synchronous movement in the seat you can reach a larger opening angle, which has the advantage that the circulation is more encouraged. By the individual adjustable pressure you can adapt the chair to the different body weights, and you can work for more than eight hours without getting tired. |
| Base | Plastic base, Ø 640 mm, black | Very stable. |
| Castors | Double castors, hard. | For soft floors. |
| Seat cover | Tec in different colours, high- quality, hard-wearing fabric cover, 100% polypropylene, 30.000 martindale, 230g/rfm Lucia in different colours, high- quality, hard- wearing fabric cover, 100% polypropylene, 100.000 martindale, 400g/rfm | |
| Pelvic support | - | When sitting upright, the rear of the sea pad has a raised section to support the spine and to relieve the muscles |
| Seat depth adjustment | Sliding seat, adjustment range 50 mm. | Allows you to alter the distance between the front edge of the seat and backrest |
| Seat inclination adjustment | | Allows the entire seat to be tilted by up to 4°. It supports active seating - this keeps the pelvis more upright and the spine retains its original "double-S" shape. |

Technical data sheet 3476

Specification Swivel chair

| Dimensions in mm | Backrest: | H: | 620 |
|------------------|-----------|-------------------|----------|
| | Seat: | H: | 420-550 |
| | | W: | 460 |
| | | D: | 445 |
| | Total: | | 4400 |
| | | H: | 1190 |
| | | W (no ArmR) | 460 |
| | | W (ArmR): | 720 |
| | | D: | 680 |
| Packaging data | Weight: | kg | 19,5 |
| | Volume: | m³ | 0,2 |
| Warranty | | 3 years exchange | warrantv |
| | | z , zz z ononango | |



.....

Technical data sheet 3476

Specification Swivel chair

| Dimensions in mm | Backrest: | H: | 620 |
|------------------|-----------|-------------|---------|
| | Seat: | H: | 420-550 |
| | | W: | 460 |
| | | D: | 445 |
| | Total: | H: | 1190 |
| | | W (no ArmR) | 460 |
| | | W (ArmR): | 720 |
| | | D: | 680 |
| Packaging data | Weight: | kg | 19,5 |
| | Volume: | m³ | 0,2 |
| | | | |



| Options | | Benefit |
|----------|---|---|
| Castors | Soft double castors | For hard floors |
| | | |
| Base | Aluminium base briliiant silver or polished | |
| | | |
| Armrests | Loop armrests or 3D T-armrests | You can achieve relief for the neck by using the height adjustment of the armrests. |
| | | |