

Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 8

SDS No.: 490618

V002.0 Revision: 14.06.2016

printing date: 24.08.2017

Replaces version from: 19.02.2014

Pattex Textil Glue

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pattex Textil Glue

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Dispersion

Danish PR-number:

Not needed.

1.3. Details of the supplier of the safety data sheet

Henkel Norden AB

Adhesives SE

Gustavslundsvägen 151 A

167 51 Bromma

Sweden

Phone: +46 (0) 10 480 7700

ua-productsafety.norden@henkel.com

1.4. Emergency telephone number

+46 10 480 7500 (kontortid)

+45 82 12 12 12 (giftlinjen)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation
H319 Causes serious eye irritation.

Category 2

2.2. Label elements

Label elements (CLP):



Signal word: Warning

MSDS-No.: 490618 Pattex Textil Glue Page 2 of 8

V002.0

Hazard statement:	H319 Causes serious eye irritation.
Precautionary statement:	P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand.
Precautionary statement: Prevention	P280 Wear eye protection.
Precautionary statement: Response	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Contact adhesive

Base substances of preparation:

Polyvinyl acetate dispersion

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Aluminum chloride, basic 1327-41-9	215-477-2	1- < 3 %	Eye Dam. 1 H318 Met. Corr. 1 H290

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remains (intensive smarting, sensivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

MSDS-No.: 490618 Pattex Textil Glue Page 3 of 8

V002.0

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

For waste disposal see section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Dispersion

MSDS-No.: 490618 Pattex Textil Glue Page 4 of 8

V002.0

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Denmark

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminum chloride, basic 1327-41-9		1	Threshold Limit Values (TLV):		GV (DK)

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

material thickness > 0.1 mm

Perforation time > 480 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

Danish Code Number:

00-1 (1993)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid white
Odor characteristic

Odour threshold No data available / Not applicable

pH No data available / Not applicable
Initial boiling point No data available / Not applicable
Flash point No data available / Not applicable
Decomposition temperature No data available / Not applicable

MSDS-No.: 490618 Pattex Textil Glue Page 5 of 8

V002.0

Vapour pressure No data available / Not applicable

Density 1,5 g/cm³

(20 °C (68 °F))

Bulk density No data available / Not applicable

Viscosity 30.000 - 45.000 mPa.s

()

Viscosity (kinematic) No data available / Not applicable No data available / Not applicable Explosive properties Solubility (qualitative) No data available / Not applicable No data available / Not applicable Solidification temperature No data available / Not applicable Melting point Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable No data available / Not applicable Partition coefficient: n-octanol/water Evaporation rate No data available / Not applicable No data available / Not applicable Vapor density Oxidising properties No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Eye irritation:

Causes serious eye irritation.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Aluminum chloride, basic	LD50	> 2.000 mg/kg	oral		rat	OECD Guideline 401 (Acute
1327-41-9						Oral Toxicity)

MSDS-No.: 490618 Pattex Textil Glue Page 6 of 8

V002.0

Acute dermal toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Aluminum chloride, basic	LD50	> 2.000 mg/kg	dermal		rat	Hoechst Test
1327-41-9						

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Aluminum chloride, basic	not irritating		rabbit	OECD Guideline 404 (Acute
1327-41-9				Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Aluminum chloride, basic 1327-41-9	highly corrosive			
Aluminum chloride, basic 1327-41-9	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Aluminum chloride, basic 1327-41-9	Category 1 (irreversible effects on the eye)	1 s	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following. Do not empty into drains, soil or bodies of water.

Special danish ecological regulations:

There should be precautions taken against environmental damage caused by articles containing this product.

12.1. Toxicity

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
CIAS I VO.	ty pe		Study	tillic		
Aluminum chloride, basic	LC50	> 1.000 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
1327-41-9					Danio rerio)	203 (Fish, Acute
						Toxicity Test)
Aluminum chloride, basic	EC50	98 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
1327-41-9						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Aluminum chloride, basic	EC50	1,5 - 2 mg/l	Algae	96 h	Scenedesmus quadricauda	OECD Guideline
1327-41-9						201 (Alga, Growth
						Inhibition Test)

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Aluminum chloride, basic 1327-41-9	< 3					

12.5. Results of PBT and vPvB assessment

MSDS-No.: 490618 Pattex Textil Glue Page 7 of 8

V002.0

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

Danish Disposal:

Product is to be destroyed on Kommunekemi as organic solvent group H, card no. 3.13.

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (VOCV 814.018 VOC regulation CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 490618 Pattex Textil Glue Page 8 of 8

V002.0

National regulations/information (Denmark):

National regulations: Order No. 302 of 13 May 1993 issued by the Danish Working Environment Service

on work with codenumbered products

Danish Code Number: 00-1 (1993)

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H290 May be corrosive to metals. H318 Causes serious eye damage.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

Danish specific phrases:

The product is being used as an adhesive everywhere in general industries.