

Commercial Identity...

Brand	SAFETOOL	
Commercial Gencod	3 5512 600 3210 4	
Designation	Hand truck solid wheels	
Custom Nomenclature	87168000	
Warranty (years) :	0	

Consumer Unit ...

Height (mm)	1 120.000	Weight (g)	16 000.000
Lenght (mm)	553.000		
Depth (mm)	467.000		
Colors:	<input type="text"/>		
Presentation of C.U.:	<input type="text"/>		
Certification(s) du produit :	<input type="text"/>		



Technical Comment

Diamètre de la roue : 20 cm
 Dimensions ouvert complètement : H 112 x L 545 x P 760 cm
 fermé : 112 x 54 x 40 cm
 Plateforme fixe : 40,5 x 15,5 cm
 Plateforme rabattable : 52 x 33 cm

Product ...

Folded...		Unfolded...	
Tot. Leng.(mm)	1 100.000	Tot.Lenght (mm)	<input type="text"/>
Tot.Width (mm)	553.000	Tot.Width (mm)	<input type="text"/>
Tot.Depth (mm)	467.000	Tot.Depth (mm)	<input type="text"/>
Diameter (mm)	<input type="text"/>	Unfolded Diam.(m)	<input type="text"/>
Weight (g)	15 000		
Strenght (g)	<input type="text"/>		
Load (kg)	<input type="text"/>		
Origin	CHINE		
<input type="checkbox"/> Recyclable	<input type="checkbox"/> Instructions supplied		
<input type="checkbox"/> Perishable	<input type="checkbox"/> Assorted colours upon availability		

Cutting ...

Handles ...			
Ext. Height. (mm)	<input type="text"/>	Int. Height (mm)	<input type="text"/>
Ext. Width (mm)	<input type="text"/>	Int. Width (mm)	<input type="text"/>
Ext. Depth(mm)	<input type="text"/>	Int. Depth (mm)	<input type="text"/>
Cutting Lenght (mm)	<input type="text"/>	Material	<input type="text"/>
Screws ...			
Diameter (mm)	<input type="text"/>	Dist. Screw-Handles (mm)	<input type="text"/>
Material	<input type="text"/>	Dist. Screw-Point (mm)	<input type="text"/>
Blades ...			
Height (mm)	<input type="text"/>	Material	<input type="text"/>
Width (mm)	<input type="text"/>	HRC Handles	<input type="text"/>
Depth (mm)	<input type="text"/>	Shearing	<input type="text"/>
<input type="checkbox"/> Divisible blade	Nb. of divisible segments	<input type="text"/>	

Heated & Electrical Devices ...

Tension (V)	<input type="text"/>	# Conductors	<input type="text"/>	Batteries supplie	<input type="checkbox"/>
Intensity (A)	<input type="text"/>	Ø Cond. (mm²)	<input type="text"/>	Adapt. supplied	<input type="checkbox"/>
Power (W)	<input type="text"/>			Cord supplied	<input type="checkbox"/>

Card & Blister ...

Height (mm)	<input type="text"/>
Width (mm)	<input type="text"/>
Depth (mm)	<input type="text"/>
Thickness(mm)	<input type="text"/>
Weight (g)	<input type="text"/>
Lock	<input type="checkbox"/>
Material	<input type="text"/>

SPCB ...

Lenght (mm)	<input type="text"/>
Width (mm)	<input type="text"/>
Height (mm)	<input type="text"/>
Thickness (mm)	<input type="text"/>
Packing	1
Weight (g)	0
Net Weight (g)	16 000
Gross Weight (g)	16 000

PCB ...

Lenght (mm)	1 120
Width (mm)	553
Depth (mm)	467
Thickness (mm)	<input type="text"/>
Packing	1
Weight (g)	0
Net Weight (g)	16 000
Gross Weight (g)	16 000

Pallet ...

Lenght (mm)	<input type="text"/>
Width (mm)	<input type="text"/>
Height (mm)	<input type="text"/>
Type	<input type="text"/>
# packet/pallet	6
# packet/layer	6
# layer	1
Weight (g)	0
Net Weight (g)	96 000
Gross Weight (g)	96 000