

**Product Datasheet model skyguard NT 9175 275**



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

<p><b>Product characteristics</b></p>	<ul style="list-style-type: none"> <li>* An improved spectacle with all-round protection</li> <li>* An injection moulded TPU frame increase wearer protection levels through minimising the risk of particle ingress</li> <li>* The flexible, closed-pore soft components enables a customised, individual fit</li> <li>* Easy to clean to promote long term use</li> <li>* Individual side arm inclination</li> </ul>
<p><b>Technical details</b></p> <p><b>Frame</b></p> <p>Material Colour</p> <p>Material Colour</p>	<p><b>Front piece</b> PP grey</p> <p><b>TPU layer</b> TPU orange</p>

Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Low-energy impact	F (45 m/s)
Conformity symbol	CE
<b>Material</b>	<b>Side piece</b> PBT+PC
<b>Features</b>	adjustable inclination
<b>Colour</b>	grey
<b>Material</b>	<b>Temple</b> PBT+PC
<b>Colour</b>	grey
Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Tested acc. to DIN	DIN
Conformity symbol	CE
No. of certificat. body	0196
<b>Lens</b>	
<b>Material</b>	PC
<b>Thickness</b>	2,1 mm
<b>Coating</b>	supravision HC-AF
<b>Colour</b>	clear

	<b>Marking</b>
Filter	2-1,2 ( DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE
<b>Miscellaneous</b>	
Weight	43 g
Packing	5 spectacles 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170