

**Product Datasheet model pheos 9192 225**



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

<p><b>Product characteristics</b></p>	<ul style="list-style-type: none"> <li>* Modern fashion-look</li> <li>* Duo spherical lens provides excellent all round vision</li> <li>* Eye plus-protection protects the eyebrows through an additional chamfer at the upper range</li> <li>* A slim temple geometry enables a comfortable wearing of earmuffs, helmets and caps</li> <li>* Outstanding ventilation ensures a well eye climate</li> <li>* Temple ends with non-slip components</li> </ul>
<p><b>Technical details</b></p> <p><b>Frame</b></p> <p>Material</p> <p>Features</p> <p>Colour</p>	<p><b>Front piece/Temple</b></p> <p>POM/TPE</p> <p>excellent ventilation</p> <p>black-green</p>

<b>Manufacturer's ID code</b>	<b>Marking</b> W
<b>Applicable EN norm</b>	166
<b>Low-energy impact</b>	F (45 m/s)
<b>Conformity symbol</b>	CE
<b>Lens</b>	
<b>Material</b>	PC
<b>Thickness</b>	2,1 mm
<b>Coating</b>	supravison HC-AF
<b>Colour</b>	clear
<b>Filter</b>	<b>Marking</b> 2C-1,2 (DIN EN 170)
<b>Manufacturer's ID code</b>	W
<b>Optical class</b>	1
<b>Low-energy impact</b>	F (45 m/s)
<b>Surface resistance to fine particles</b>	K
<b>Antifog</b>	N
<b>Conformity symbol</b>	CE
<b>Miscellaneous</b>	
<b>Weight</b>	30 g
<b>Packing</b>	5 spectacles per box 160 spectacles per cardboard box
<b>Standards</b>	DIN EN 166 + DIN EN 170