

Product data sheet folding mask FFP1 - uvex silv-Air 3110



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, 90766 Fürth, Germany

Product features	<ul style="list-style-type: none"> • Optimised shape • Soft material edges for high wearing comfort • The adjustable head band clips offer easy handling and comfortable fit • Exhalation valve for reduced build-up of heat and moisture inside the mask • Flexible and adjustable nose piece • Mask fulfils the requirements of the dolomite dust test (D) • Compatible with uvex safety eyewear
Materials	Head band: elastic textile Nose piece: PP Headband clips: PP Filter / mask: Melt Blown PP, Polyester Sealing lip: EVA foam Valve: ABS

Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 4 times the respective limit values.	Agriculture, food industry, quarries, cement plants, construction, softwood processing, dust and fumes of calcium carbonate, graphite, gypsum, chalk, cement, plaster, marble, zinc oxide, plant dust, cellulose, sulphur, cotton, ferrous metal respirable dust, coal dust with less than 10% free silicon oxide.
Weight	17g
Standard	EN 149:2001 + A1:2009

Versions/Colour:

Artikle-No.	Colour/Version	Retail unit
8733.110	Folding mask FFP1, white with valve	15 pieces per box