

1. Product and Company Identification

Material name HP Color LaserJet CE260A-X Black Print Cartridge

This product is a black toner preparation that is used in HP Color LaserJet CP4525, CP4025 Use of the preparation

series printers.

Version #

15-Oct-2009 **Revision date**

Company identification Hewlett-Packard Company

3000 Hanover Street Palo Alto, CA 94304-1185 **United States**

Telephone 650-857-1501

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 **HP Customer Care Line**

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

Oct 15, 2009 Date prepared

2. Hazards Identification

Acute health effects

Skin contact Unlikely to cause skin irritation. May cause transient slight irritation Eve contact

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Use

of this product as intended does not result in inhalation of excessive amounts of dust.

Ingestion Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

Potential health effects

Routes of exposure Potential routes of exposure under normal use conditions are skin, eye contact and inhalation.

Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions.

Chronic health effects Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this

product as intended does not result in inhalation of excessive amounts of dust.

Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly Carcinogenicity

carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not

present this carcinogenic risk.

Other information This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU

Directive 1999/45/EC, as amended.

This preparation contains no component classified as Persistent, Bioaccumulative, and Toxic (PBT) or very Persistent and very Bioaccumulative (vPvB) as defined under Regulation (EC)

1907/2006.

3. Composition / Information on Ingredients

Component/substance	CAS number	% by weight	
Styrene acrylate copolymer	Trade Secret	< 85	
Wax	Trade Secret	< 10	
Carbon black	1333-86-4	< 6	
Amorphous silica	7631-86-9	< 2	

Material name CE260A-X MSDS US Creation date Sep 22, 2009 Version number 1 1/5



4. First Aid Measures

First aid procedures

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for

at least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.

Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

5. Fire Fighting Measures

Flash point and method Not applicable

Hazardous combustion

products

Carbon monoxide and carbon dioxide.

Like most organic material in powder form, toner can form explosive dust-air mixtures when Flammable properties

finely dispersed in air.

Extinguishing media

Suitable extinguishing

media

CO2, water, or dry chemical

Unsuitable extinguishing

media

None known.

Unusual fire and explosion

hazard

Like most organic material in powder form, toner can form explosive dust-air mixtures when

finely dispersed in air.

Protection of firefighters

Protective equipment and

precautions for firefighters

If fire occurs in the printer, treat as an electrical fire.

Special firefighting procedures

None established.

6. Accidental Release Measures

Personal precautions

Minimize dust generation and accumulation.

Environmental precautions

Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

Other information

Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance

with federal, state, and local regulations.

7. Handling and Storage

Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use

with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from strong

oxidizers. Store at room temperature.

8. Exposure Controls / Personal Protection

Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH

(TWA/TLV): 10 mg/m3

Personal protective equipment

General No personal respiratory protective equipment required under normal conditions of use.

Material name CE260A-X MSDS US Creation date Sep 22, 2009 Version number 1 2/5



9. Physical & Chemical Properties

Appearance Fine powder

Black Color

Slight plastic odor Odor **Odor threshold** Not available. Not available. **Physical state**

Form solid

Not applicable Hq Not available. **Melting point** Freezing point Not available. **Boiling point** Not applicable Flash point Not applicable Not applicable **Evaporation rate** Not available. **Flammability** Flammability limits in air, Not available.

upper, % by volume

Flammability limits in air,

lower, % by volume

Not flammable

Vapor pressure Not applicable Vapor density Not applicable 1 - 1.2 (H2O = 1)Specific gravity Relative density Not available.

Solubility (water) Negligible in water. Partially soluble in toluene and xylene.

Partition coefficient

(n-octanol/water)

Not available.

Not applicable **Auto-ignition temperature Decomposition temperature** Not available.

Softening point 176 - 266 °F (80 - 130 °C)

Viscosity Not applicable

Other information Decomposition temperature: > 200 ° C

10. Chemical Stability & Reactivity Information

Chemical stability Stable under normal storage conditions.

Conditions to avoid Imaging Drum: Exposure to light

Incompatible materials Strong oxidizers

Hazardous decomposition

products

Carbon monoxide and carbon dioxide.

Possibility of hazardous

reactions

Will not occur.

11. Toxicological Information

Oral toxicity LD50/oral/rat >2000 mg/kg; (OECD 401); Not harmful.. Not classified for acute oral toxicity

according to EU Directive 67/548/EEC and 1999/45/EC.

No information available. Inhalation toxicity

Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and

1999/45/EC.

Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU Eye irritation

Directive 67/548/EEC and as amended.

Material name CE260A-X MSDS US Creation date Sep 22, 2009 Version number 1 3/5



Sensitization Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and

OSHA HCS (US).

Chronic toxicity No information available.

Carcinogenicity Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans,

Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation. None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or

OSHA.

Mutagenicity Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Reproductive toxicity Not classified as toxic according to EU Directive 67/548/EEC and as amended, California

Prop. 65, and DFG (Germany).

12. Ecological Information

Ecotoxicity 96.00 Hours, LL50 > 1000 mg/l, rainbow trout

Persistence and degradability Not available.

13. Disposal Considerations

Disposal instructionsDo not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely

dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal,

state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkiet and LaserJet supplies. For more information and to determine

if this service is available in your location, please visit http://www.hp.com/recycle.

14. Transport Information

Not available.

General Not a dangerous good under United States DOT, IATA, ADR, IMDG, or RID.

15. Regulatory Information

US federal regulations US EPA TSCA Inventory: All chemical substances in this product comply with all rules or

orders under TSCA.

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely

hazardous substance

No

Section 311 hazardous

chemical

No

under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South

Korea, New Zealand, and China.

16. Other Information

HMIS® ratings Health: 1

Flammability: 1 Physical hazard: 0

Material name CE260A-X

Creation date Sep 22, 2009

Version number 1

MSDS US

4 / 5



NFPA ratings Health: 1

Flammability: 1 Instability: 0

Issue date Oct 15 2009 10:57AM

Revision

Manufacturer information Hewlett-Packard Company

11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation

(29 CFR 1910.1200).

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in

Section 1 above and may not meet regulatory requirements in other countries.

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name CE260A-X

Creation date Sep 22, 2009

Version number 1

MSDS US

5 / 5